

Riflescopes Product Sheet

	Milescopes i		
Photo	Model	Color	Spec
HOLD ZERO	NF ATACR 1-8X 24MM	вк	Magnification Range: 1-8x Focal Plane: First Focal Plane (F1/FFP) Parallax Adjustment: Fixed @ 125 m Eye Relief: 3.7 in/95 mm Field of View @ 100 yd or m: 1x: 96.1 ft/32.0 m 8x: 13.1 ft/4.4 m
HOLD ZERO	NF ATACR 1-8X 24MM	FDE	Body Tube Diameter: 34mm Illumination: 12 levels Battery: CR2032 Overall Length: 256 mm Weight: 595 g
HOLD ZERO	SIG SAUER TANGO6T 1-6X24MM	вк	Magnification Range: 1-6x Focal Plane: First Focal Plane (F1/FFP) Parallax Adjustment: Fixed @ 150 m Eye Relief: 3.9/4.1inch Field of View @ 100 yd or m: 1x: 105.8 ft 6x: 17.7ft
HOLD ZERO	SIG SAUER TANGO6T 1-6X24MM	FDE	Body Tube Diameter: 30mm Illumination: 11 levels Battery: CR2032 Overall Length: 285 mm Weight: 592 g
HOLD ZERO	EOTECH VUDU 1-6X24MM	вк	Magnification Range: 1-6x Focal Plane: First Focal Plane (F1/FFP) Parallax Adjustment: Fixed @ 150 m Eye Relief: 3.27–3.94" Field of View @ 100 yd or m: 1x: 102.4 ft (31.2m) 6x: 16.7 ft (5.09m) Body Tube Diameter: 30mm Illumination: 10 levels Battery: CR2032 Overall Length: 270 mm Weight: 570 g
HOLD ZERO	STRIKE EAGLE 1-6X24	вк	Magnification Range: 1-6x Focal Plane: Second Focal Plane Parallax Adjustment: Fixed @ 100 yds Eye Relief: 3.5 inches Field of View: 116.5-19.2 ft @100 yds Body Tube Diameter: 30mm Battery: CR2032 Overall Length: 10.5 inches Weight: 18.5 oz

NEW!	STRIKE EAGLE 1-8X24	вк	Magnification Range: 1-8x Focal Plane: Second Focal Plane Parallax Adjustment: Fixed @ 100 yds Eye Relief: 3.5 inches Field of View: 109 -14.4 ft @100 yds Body Tube Diameter: 30mm Battery: CR2032 Overall Length: 10.0 inches Weight: 17.6 oz
NEW! RAZOR' HD GEN II-E HOLD ZERO	RAZOR HD GEN II-E	FDE	Full Original Packaging Box Magnification Range: 1-6x Focal Plane: Second Focal Plane Parallax Adjustment: Fixed @ 100 yds Eye Relief: 4 inches Field of View: 115.2-20.5 ft/100 yds Body Tube Diameter: 30mm Battery: CR2032 Overall Length: 10.1 inches Weight: 21.5 oz
	RAZOR HD GEN III	FDE	Magnification Range: 1-10x Focal Plane: First Focal Plane Parallax Adjustment:Fixed @150 yds Eye Relief: 3.6 inches Field of View: 116-11.7 ft @100 yds Body Tube Diameter: 34mm Battery: CR2032 Overall Length: 10.1 inches Weight: 21.5 oz
HOLD ZERO	DIAMONDBACK 4-16X44	вк	Magnification Range: 4-16x Focal Plane: First Focal Plane Parallax Adjustment: 20 yards to infinity Eye Relief: 3.8 inches Field of View: 116-11.7 ft @100 yds Body Tube Diameter: 30mm Overall Length: 14.06 inches Weight: 23.1 oz
HOLD ZERO	DIAMONDBACK 6-24X50	вк	Magnification Range: 6-24x Focal Plane: First Focal Plane Parallax Adjustment: 10 yards to infinity Eye Relief: 3.9 inches Field of View: 18-4.5 ft/100 yds Body Tube Diameter: 30mm Overall Length: 14.28 inches Weight: 24.6 oz
HOLD ZERO	VENOM 5-25X56	вк	Magnification Range: 5-25x Focal Plane: First Focal Plane Parallax Adjustment: 15 yards to infinity Eye Relief: 3.6 inches Field of View: 21.2-4.7 ft @100 yds Body Tube Diameter: 34mm Overall Length: 15.3 inches Weight: 35 oz.

		1	
HOLD ZERO	CROSSFIRE II 3-9X40	вк	Magnification Range: 3-9x Focal Plane: Second Focal Plane Parallax Adjustment: 100 yards Eye Relief: 3.8 inches Field of View: 34.1-12.6 ft/100 yds Body Tube Diameter: 30mm Overall Length: 12.2 inches Weight: 14.8 oz
	CROSSFIRE II 6-24X50 AO	вк	Magnification Range: 6-24x Focal Plane: Second Focal Plane Parallax Adjustment: 10 yards to infinity Eye Relief: 4.0 inches Field of View: 17.3-4.4 ft/100 yds Body Tube Diameter: 30mm Overall Length: 14.5 inches Weight: 23.6 oz
	NF NXS 5.5-22X56MM	ВК	Magnification Range: 5.5-22x Focal Plane: First Focal Plane (F1/FFP) Eye Relief: 3.9 in/99 mm Field of View @ 100 yd or m: 5.5x: 17.5 ft/5.8 m 22x: 4.7 ft/1.6 m Body Tube Diameter: 30mm Battery: CR2032 Overall Length: 385mm Weight: 952 g
HOLD ZERO ORIGINAL	5 TACTIX 1-6×24 THUNDER RANCH	ВК	Magnification Range: 1-6x Focal Plane: Second Focal Plane Eye Relief: 3.5in/90mm Field of View: 111.2ft - 18.33ft/100 yds Body Tube Diameter: 30mm Battery: CR2032 Overall Length: 10.25in Weight: 22.2oz
HOLD ZERO ORIGINAL	Primary Arms SLx 1-6x24mm	вк	Magnification Range: 1-6x Focal Plane: Second Focal Plane Eye Relief: 4.00 in Field of View: Low: 120 ft / High: 20 ft/100 yds Body Tube Diameter: 30mm Battery: CR2032 Overall Length: 10.4 In Weight: 17.9 oz.
HOLD ZERO ORIGINAL		вк	Magnification Range: 3-9x Focal Plane: Second Focal Plane Eye Relief: 3.7 inches Field of View: 31-11 ft (9.4-3.3m) @100 yds Body Tube Diameter: 30mm Weight: 21 oz

<u></u>			
HOLD ZERO ORIGINAL	Bushnell 1-4x24 AR	вк	Magnification Range: 1-4x Focal Plane: Second Focal Plane Eye Relief: 3.5 inches Field of View: 112ft @ 1X to 27ft @ 4X Body Tube Diameter: 30mm Weight: 18 oz
	Trijicon VCOG 1-6x24	вк	Magnification Range: 1-6x Focal Plane: First Focal Plane Eye Relief: 4 inches Field of View: 15.9 - 95 ft at 100 yds Body Tube Diameter: 30mm Overall Length: 10.05 inches Weight: 23.3 oz
Hamp Bosenins	LEUPOLD HAMR	вк	4x Magnification 24mm Objective lens diameter. Velocity Drop Compensator. Scope length 14cm Weight 420g. Eye Relief 2.7 inches. Field of View @ 100 yards (ft) 32.00 Power Source: 2x CR2032
Leurote Leurote	LEUPOLD LCO + DEVO	вк	LCO Dot Sight: 1Moa Dot Power Supply: 1x3v CR123A Lithium Battery Dimensions: 91.4*57.1*61.2 mm Weight: 8.9oz(252.3g) Devo 6x Magnification Objective Lens Diameter: 20 Millimeters Dimensions: 2.87 x 5 x 8 inches
	Trijicon ACOG 4X32	BK/TAN	Magnification: 4x Reticle Color: Red/Green Eye Relief: 1.5 in Field of View: 36.8 ft. @ 100 yds. Illumination: Fiber Optics Mount: Flattop Thumbscrew Mount (TA51) or Larue LT100 QD mount Size: 151 x 73 x 50mm Weight:405g
HOLD ZERO	New Trijicon ACOG 4X32 (2023 New Verison)	BK/TAN	Magnification: 4x Reticle Color: Red/Green Eye Relief: 1.5 in Field of View: 36.8 ft. @ 100 yds. Shockproof: 1200g Waterproof: IPX7 Illumination: Fiber Optics Mount: Flattop Thumbscrew Mount (TA51) or Larue LT100 QD mount Size: 151 x 73 x 50mm Weight:405g

	1	_	
HOLD ZERO	Trijicon TA02 LED	вк	Magnification: 4x Reticle Color: Red Eye Relief: 1.5 in Field of View: 36.8 ft. @ 100 yds. Illumination: RED LED Mount: Flattop Thumbscrew Mount (TA51) Size: 151 x 73 x 50mm Weight: 18.1 oz
HOLD ZERO	Trijicon TA11	вк	Magnification: 3.5x Reticle Color: Red Eye Relief: 2.39 in Field of View: 28.9 ft at 100 yds Illumination: Fiber Optics Mount: Flattop Thumbscrew Mount (TA51) or Larue LT100 QD mount Size: 183 x 73 x 50mm Weight: 14 oz
	Specter OS4x	вк	Magnification: 4x Eye Relief: 70mm Field of View: 6.5' Illumination: 5 levels Battery type: CR1602 (3v Lithium) Mount: Mil-Std-1913 'Picatinny Rail' Size: 153mm L x 67mm W x 65mm H Weight:515g
NEW!	New DR 1-4x		Magnification: 4x / 1x Aiming Dot diameter: 1.5 MoA @ 4x, 6 MoA @ 1x Field of View: 26 deg @ 1x, 6.5 deg @ 4x Eye Relief: 70mm Nominal focus:150m @ 4x, 70m @ 1x Illumination: 5 levels Battery type: CR1602 (3v Lithium) Mount: Mil-Std-1913 'Picatinny Rail' Size: 158 x 56 x 65mm Weight: 626g
HOLD ZERO	New DR 1.5-6x	вк	Magnification: 6x / 1.5x Aiming Dot diameter:1.5 MoA @ 6x, 6 MoA @ 1.5x Field of View: 16 deg @ 1.5x, 4 deg @ 6x Eye Relief: 70mm Nominal focus:300m @ 6x, 105m @ 1.5x Illumination: 5 levels Battery type: CR1602 (3v Lithium) Mount: Mil-Std-1913 'Picatinny Rail' Size: 19.6 x 60 x 66mm Weight: 813g
HOLD ZERO	ELCAN specterDR 1-4x	вк	Magnification: 4x / 1x Aiming Dot diameter: 1.5 MoA @ 4x, 6 MoA @ 1x Field of View: 26 deg @ 1x, 6.5 deg @ 4x Eye Relief: 70mm Nominal focus:150m @ 4x, 70m @ 1x
HOLD ZERO	ELCAN specterDR 1-4x	TAN	Illumination: 5 levels Battery type: CR1602 (3v Lithium) Mount: Mil-Std-1913 'Picatinny Rail' Size: 158 x 56 x 65mm Weight: 626g

			1
HOLD ZERO	ELCAN specterDR 1.5-6x	вк	Magnification: 6x / 1.5x Aiming Dot diameter:1.5 MoA @ 6x, 6 MoA @ 1.5x Field of View: 16 deg @ 1.5x, 4 deg @ 6x Eye Relief: 70mm Nominal focus:300m @ 6x, 105m @ 1.5x
HOLD ZERO	ELCAN specterDR 1.5-6x	TAN	Illumination: 5 levels Battery type: CR1602 (3v Lithium) Mount: Mil-Std-1913 'Picatinny Rail' Size: 19.6 x 60 x 66mm Weight: 783g
	NF 1.54" Scope Mount	вк	
	NF 1.54" Scope Mount	FDE	MIL-SPEC UltraMount MATERIAL: Aluminum
	NF 1.93" Scope Mount	FDE	RING DIAMETER: 30mm/34mm RING HEIGHT TO CENTER: 1.54"/1.93" WEIGHT: 167g/173g
	NF 1.93" Scope Mount	вк	
	COMM Offset RMR&T2 Mount	BK/FDE	
	COMM TOP RMR Mount	BK/FDE	MATERIAL: Aluminum RING DIAMETER: 30mm/34mm RING HEIGHT TO CENTER: 1.54"/1.70"/1.93" WEIGHT: 220g Important: (30mm: 1.70"/1.93", 34mm: 1.54"/1.70")
J. J	COMM TOP T2 Mount	BK/FDE	

	FAST COG	BK/FDE	MATERIAL: Aluminum
and the same of th	Geissele Mount 1.54" / 1.93"	BK/FDE	MATERIAL: Aluminum RING DIAMETER: 30mm RING HEIGHT TO CENTER: 1.54"/1.93" WEIGHT: 157g/163g
	Scopeswitch Mount (30mm / 34mm)	BK/FDE	MATERIAL: Aluminum RING DIAMETER: 30mm/34mm RING HEIGHT TO CENTER: 1.93" WEIGHT: 280g
	FAST LPVO	BK/FDE	MATERIAL: Aluminum RING DIAMETER: 30mm RING HEIGHT TO CENTER: 2.05" WEIGHT: 210g
	LEAP/08 (1.54" 30mm) LEAP/09 (1.93" 34mm)	BK/FDE	MATERIAL: Aluminum RING DIAMETER: 30mm/34mm RING HEIGHT TO CENTER: 1.54"/1.93 WEIGHT: 170g/190g
	Spuhr SP-3002	ВК	Ring Size: 30mm Tilt: 0 MIL / 0 MOA Height: 38mm(1.5in) Length: 126mm(4.96in) 10-degree wedge included